



WWW.DELOCK.COM

DATA SHEET



PCI Card > Dual Channel FireWire A 2 port (IEEE 1394a)

Description

The Delock FireWire PCI card by IOI expands your PC by two external FireWire A ports. You can connect several FireWire devices like e.g. external enclosures with integrated hard disk or CD drive, camcorder etc. to the card.



Ref. 89171

EAN 4043619891719

Country of origin China
Customs tariff number 84733020

Images



Specification

- IOI item number: IOI-4601-21
- 2 x external FireWire A (IEEE 1394a)
- 1 x intern Bus power connector with mini 4 Pin DC +
 12 V power connector
- Chipset: 2 x TI TSB43AB22A
- Data transfer rate up to 800 Mb/s (400 Mb/s / Channel) per Port
- 32-Bit PCI standard 2.2
- Supports OHCI 1.1 standard
- Dual channel OHCI

System requirements

- Windows 98SE/Me/2000/XP/Server-2003/Vista/7, Mac OS 10.5 or higher, Linux Kernel 2.6
- One free PCI slot

Package content

- PCI Express Card 4x external FireWire A
- Y-cable power Molex > Molex 4 Pin + 3½ FDD

Package

Antistatic cover

© 2011 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.

